

OMNIKEY® Contactless Reader



OMNIKEY® 5321 USB

The OMNIKEY® 5321 is a dual interface PC-linked reader that reads/writes to both a 13.56 MHz contactless smart card and virtually any contact smart card. The dual interface feature economically supports end-user environments where both contactless and contact smart card technology may be in use. The reader supports contactless smart cards with up to 848kbps in the fastest ISO 14443 transmission mode.

Contactless Smart Card support:

- NXP: MIFARE®, DESFire, SMART-MX, and ICODE
- HID: iCLASS®
- Texas Instruments: TagIT®
- ST Micro: x-ident, SR 176, SR 1X 4K
- Infineon: My-d (in secure mode UID only)
- Atmel: AT088RF020
- KSW MicroTech: KSW TempSens
- Contactless 2048 bit key generation in RSA mode (JCOP / SMART-MX)

Host Interface	
Host Interface	USB 2.0 CCID ¹ (also supports USB 1.1)
Transmission speed	12 Mbps (USB 2.0 full speed)
Power supply	Bus powered
Smart Card Interface	
Standards	ISO 7816 & EMV ² 2000 Level 1
Protocols	T=0, T=1, 2-wire: SLE 4432/42 (S=10), 3-wire: SLE 4418/28 (S=9), I ² C (S=8)
Card size	ID-1 (full-size)
Smart Card interface speed	420 Kbps (when supported by card)
Smart Card clock frequency	Up to 8 MHz
Supported card types	5V, 3V and 1.8V Smart Cards ISO 7816 Class A, AB and C
Power to Smart Card	60 mA
Smart Card detection	Movement detection with auto power-off / Autom. Detection of smart card type / Short circuit and thermal protection
8 Pin Handling	C4 / C8 supported
Contactless (RFID) Smart Card Interface	
ISO 14443 A with 848 Kbps transmission rate (depending on card)	
ISO 14443 B with 848 Kbps transmission rate (depending on card)	
ISO 15693 with 26 Kbps transmission rate (depending on card)	
Options	
Customer specific logo or label	On Request
Customer specific colors	On Request
Other Features	
Status indicator	Dual color LED
Reader Board	Also available as PCB

Supported APIs	
PC/SC driver	
CT-API (on top of PC/SC, for contact interface)	
OCF (on top of PC/SC, for contact interface)	
Synchronous API (on top of PC/SC)	
PC/SC Driver Support	
Windows® 98 / ME, 2000 / XP (32bit), 2003 Server	
Windows® CE 5.0 / CE.NET (depending on hardware)	
Windows® XP 64bit (AMD64, EM64T, IA64)	
Windows® Vista (32bit / 64bit)	
Linux®	
Mac® OS X (for contact interface only)	
Hardware Specifications	
Color	Dark grey
Dimensions (LxWxH)	115 x 96.5 x 25.5 mm 3.78" x 3.07" x .031"
Weight	Approx. 160 gr / 5.64 oz
Operating temperature	0°-55°C / 32-131°F
Operating humidity	10-90% rH
Composition	ABS
Connector cable	180 cm / 70.9"
Durability	100.000 Insertions
Meantime between failure (MTBF)	500.000 hours
Compliance / Certification	
Microsoft WHQL ³	CE
EMV ² 2000 Level 1	FCC
ISO 7816	UL
HBCI ⁴	RoHS
USB 2.0 (USB 1.1 compatible)	WEEE
CCID (contact interface only)	
GSA Fips201 approved product list	
Safety / Environmental	

1 = Chip Card Interface Device 2 = Europay® MasterCard® Visa® 3 = Windows® Hardware Quality Lab 4 = Homebanking Computer Interface

© ASSA ABLOY ITG reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. ASSA ABLOY ITG declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification. 02.11.2007- Page: 1 of 1 This document is subject to change without notice.

ASSA ABLOY Identification Technologies GmbH • Am Klingenberg 6A • 65396 Walluf, Germany • Tel: +49 6123 791 -0 • Fax: -110 • info@aitg.com • www.aitg.com

